

CHRYSO[®] EXCEM C

Polymer Modified Non-Shrink Admixture For Injection Cement Grouting



Description

EXCEM-C is specially formulated non-shrink grouting aid. It is a free flowing powder for addition to neat cement mixes. It plasticizes the mix, allowing for substantial reduction in water without affecting the fluidity, thus improving the strength and impermeability of the grout. During the setting period of the grout, it produces controlled expansion to compensate the normal drying shrinkage of cement. This ensures complete filling of voids and prevents formation of porous sections. It also imparts surface active properties and controlled volume increase during reaction; thus even the smallest cracks and pores can be impregnated.

Indicative Characteristics

Free linear Expansion, ASTM C 827	2-4%
Form	Powder
Color	Ashy Yellow
Compatibility	Can be used with all types of Ordinary Portland and blended Cements, including sulphate resistant Cement.
Consistency	EXCEM-C is formulated from carefully selected raw material and it is manufactured under control conditions to give a consistent product.
Handling	EXCEM-C is formulated from Chemicals which present no fire or health hazards.

Domains of Application

EXCEM-C is used as an admixture for Injection Grouting to effectively waterproof and stop leaks in underground structures, basements, tunnels, lift wells, retaining walls, dams, water reservoirs, pressure ducts and other water retaining structures. It is also recommended for grouting pre-stressed members

machine bases, column bases (Steel and precast concrete) anchor bolts etc. and wherever a non-settling,

non-bleeding, expanding grout is required. EXCEM-C can also be used as an additive to produce flowable Expansion (non shrink) concrete (with smaller sized graded aggregates are preferable) / mortar.

Method of Application

Mixing

Use mechanical mortar mixers, preferably of the slow speed (250-350 rpm) paddle mixer Hand mixing rarely achieves the desired result. Allow approx 5 minutes for mixing. Thorough mixing is essential for achieving maximum results. Add cement and EXCEM-C slowly into recommended amount of clean water in a mixer.

EXCEM-C is admixed with neat cement mixes to a suitable consistency and injected under pressure, preferably by a positive displacement pump through nozzles. The surface of the concrete/rock should be properly sealed / patched to prevent the grout from coming out. To get better result EXCEM-C should be mixed uniformly with dry cement for concrete and mortar..

Dosage

The rate of addition varies from 0.5% - 4% by weight of dry cement. The optimum dosage depends on the nature of the work

The information contained in this technical data sheet is given to the best of our knowledge and the results from extensive testing in order to remain as objective as possible. However, it cannot, in any case be considered as a warranty involving our liability in case of misuse or any different use of our products from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website www.chryso.com

CHRYSO India Private Limited | Registered & Corporate Office : Plot No. D -30/7, TTC Industrial Area, M.I.D.C. Turbhe, Navi Mumbai – 400705. Maharashtra, INDIA. Tel : +91 22 27685991/2



07/01/2017

For Supplies please contact:
Bils Innovations (India) Pvt. Ltd.
Delhi, India
+91-11 42175807
+91 9582307311
Online Shop @ www.bilsinnovations.com

Ideas to Reality – Rendering Quality | Ecology | Safety

CHRYSO[®] EXCEM C

Polymer Modified Non-Shrink Admixture For Injection Cement Grouting



Advantages

- Drastically improves the fluidity and flowability of the mix.
- Ensures high early strength and rapid gain of later strength
- Increased flexural and tensile strength.
- Provides additional resistance to dynamic and repetitive loading.
- Compensates cement shrinkage by controlled expansion.
- Withstands thermal movements to provide improved dimensional stability

Shelf Life & Storage

12 months from the date of manufacturing when stored in unopened, original sealed and dry condition at a temperature range from +5°C to 40°C

Packing

20kg waterproof laminated HDPE bag

Safety

- Wear hand gloves, safety shoes and safety goggles while using and handling the product.
- In case eyes or mouth are affected wash with plenty of clean water and seek medical treatment immediately.

Before use, refer to the Material Safety Data Sheet.
The MSDS is available on www.chryso.com

The information contained in this technical data sheet is given to the best of our knowledge and the results from extensive testing in order to remain as objective as possible. However, it cannot, in any case be considered as a warranty involving our liability in case of misuse or any different use of our products from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website www.chryso.com

CHRYSO India Private Limited | Registered & Corporate Office : Plot No. D -30/7, TTC Industrial Area, M.I.D.C. Turbhe, Navi Mumbai – 400705. Maharashtra, INDIA. Tel : +91 22 27685991/2



For Supplies please contact:
Bils Innovations (India) Pvt. Ltd.
Delhi, India
+91-11 42175807
+91 9582307311
Online Shop @ www.bilsinnovations.com



Ideas to Reality – Rendering Quality | Ecology | Safety